

## IM-240WPE


### Cuber, Self Contained

**Production Capacity (kg/24h) - AT 10°C, WT 10°C: 188**

**Storage bin capacity: 110 kg**



**ICE TYPE: Large cubes, Standard**



### ACCESSORIES INCLUDED

Installation kit, Legs, Scoop

### OPTIONAL EXTRAS

4HC-H water filtration, UV-C sanitization kit, internal drain pump (Pump motor kit and bracket)

### CORRESPONDING WATER FILTERS

4HC-H Twin Water Filter, 4HC Replacement Cartridge

PRODUCT SERIES: CUBE ICEMAKERS

ITEM NUMBER: M118-D003

COUNTRY OF ORIGIN: UK

Hoshizaki IM-240WPE Cube model is a self-contained water cooled ice maker producing up to 207 kg of cube ice per 24 hours.

Hoshizaki recommends that the water-cooled condenser should be connected to a closed circuit recirculating type cooling system utilizing a tower, water chiller or similar. Water make up should be via a ball valve/break tank arrangement. Whilst connecting a water-cooled condenser to a mains water (potable) supply will not affect the performance of the machine, it will most certainly cause high water use and waste of a valuable resource that is not recommended. It is likely that the connection of such units to the mains water supply may be a contravention of local water authority by-laws.

Ice cube dimensions and weight - disclaimer: The drawing is for illustration purposes only. Cube size and weight may be differ due to local installation conditions.

- Ice making system with an automatic rinse cycle
- Each ice cycle is made with fresh water
- Closed Cell System helps produce compact, hard and geometrically perfect ice
- Closed water circuit for contamination protection
- Easy external access to control panel
- Internal drain pump is retrofittable
- UV-C sanitization function is retrofittable
- System comes with a magnetic DC water pump with variable speed and that has no direct coupling, which prevents any leakage
- Removable door gasket
- Easily removable water pan assembly

#### WARRANTY PERIOD

**3 Years on Parts & Labour - based on country agreement**

#### EXTERIOR

**Stainless steel AISI 441, Galvanized steel (Rear)**

Refrigerant type: R290 / Refrigerant: 0,147 kg / CO2 equivalent: 0,441 kg


#### OPERATING CONDITIONS

Ambient temperature (minimum): 1 °C, Ambient temperature (maximum): 40 °C, Water supply pressure (minimum): 0.07MPa (0.7bar), Water supply pressure (maximum): 0.8MPa (8bar), Water supply temperature (minimum): 5 °C, Water supply temperature (maximum): 35 °C, Voltage range (Rated Voltage): ±6%

#### CERTIFICATIONS



## IM-240WPE



### TECHNICAL SPECIFICATIONS

| Cooling system | Power supply      | Electric Consumption | Electrical circuit breaker protection | Heat Rejection (AT 32°C, WT 21°C) | Production Capacity (kg/24h) - AT 10°C, WT 10°C | Production Capacity (kg/24h) - AT 21°C, WT 15°C | Production Capacity (kg/24h) - AT 32°C, WT 21°C |
|----------------|-------------------|----------------------|---------------------------------------|-----------------------------------|-------------------------------------------------|-------------------------------------------------|-------------------------------------------------|
| Water Cooled   | 1/220 - 240V/50Hz | 0,75 kW              | 5 A                                   | 1,54 kW                           | 188                                             | 178                                             | 163                                             |

### SHIPPING SPECIFICATIONS

| Width (packed) | Depth (packed) | Height (packed) | Volume (packed) | Gross weight | Width  | Depth  | Height   | Dimensions legs       | Net weight |
|----------------|----------------|-----------------|-----------------|--------------|--------|--------|----------|-----------------------|------------|
| 805 mm         | 760 mm         | 1.684 mm        | 1,03 m3         | 123 kg       | 704 mm | 665 mm | 1.510 mm | for legs add 70-110mm | 108 kg     |

Disclaimer: Every effort has been made to ensure that the information contained in this spec sheet is accurate at the time of publishing. Hoshizaki Europe BV assumes no responsibility or liability for typographical errors or omissions or for any misinterpretation of the information within the publication and reserves the right to change without notice.

Please observe: This type of icemaker is on special order only. Please take longer lead times into consideration.